

Limited-Slip Axle Additive Concentrate

Kendall® Limited-Slip Axle Additive Concentrate is a special additive used to modify the frictional characteristics of axle lubricants for use in limited-slip differentials. It helps to eliminate chatter in limited-slip differentials when added to non-limited-slip API GL-5 gear lubricants.

Applications

Limited-Slip Axle Additive Concentrate is recommended for use with non-limited-slip API GL-5 gear lubricants to eliminate chatter in limited-slip differentials. The recommended mixing ratio is one fluid ounce of Limited-Slip Axle Additive Concentrate to one pint of API GL-5 gear lubricant.

Limited-Slip Axle Additive Concentrate meets the requirements of:

- Chrysler MS-5630
- Dana 40819
- Ford EST-M2C118-A

Features/Benefits

- Helps prevent chatter in limited-slip and positraction differentials

**Supplemental
Friction Modifier
For API GL-5
Gear Lubricants**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**kendallmotoroil@
p66.com**



Limited-Slip Axle Additive Concentrate

Typical Properties

Specific Gravity @ 60°F	0.912
Density, lbs/gal @ 60°F	7.59
Flash Point (COC), °C (°F)	>149 (>300)
Pour Point, °C (°F)	<-40 (<-40)
Viscosity,	
cSt @ 100°C	9.2
SUS @ 210°F	57.0

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2012 Phillips 66 Company. Kendall, the Two Finger logo, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.