



Food Machinery Grease

Food Machinery Grease is a high-quality, food-grade, aluminum complex grease specially developed for use on food processing, bottling and packaging equipment where there is the possibility of incidental food contact.

Food Machinery Grease is manufactured with high-quality paraffinic base oils thickened with aluminum complex soap. It is compounded with special food-grade additives to provide excellent extreme-pressure and antiwear properties, excellent oxidation resistance, protection against rust and corrosion, and good adhesion to metal surfaces. It has excellent resistance to water washout and provides excellent rust and corrosion protection in applications where the equipment is exposed to fruit acids, chemicals or saline solutions.

Food Machinery Grease meets the requirements of U.S. FDA Regulation 21 CFR 178.3570 and former 1998 USDA H1 guidelines for incidental food contact. It is registered by NSF International as an H1 lubricant.

Applications

- Machinery used in canneries, meat packing plants and poultry plants
- Food processing equipment
- Bottling plants
- Seamers

Features/Benefits

- Registered as H1 by NSF International
- Excellent oxidation resistance
- Excellent resistance to water washout
- Good extreme-pressure and antiwear properties
- Protects against rust and corrosion
- Good adhesion to metal surfaces
- Nonstaining
- Suitable for use over a wide range of operating temperatures

Note: *Aluminum complex greases have an inherent tendency to bleed a small amount of oil during storage. Containers of Food Machinery Grease should be stored in a temperature-controlled environment to minimize oil separation.*

**Aluminum Complex
Food Machinery
Grease; NSF H1
Registered**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**Technical Hot Line:
1-877-445-9198**

**International
Customer Service:
+1-832-486-3363
+1-832-486-3870**

**E-mail address:
lubricants@
conocophillips.com**

www.conocophillipslubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

Food Machinery Grease

Typical Properties

NLGI Grade	2
Thickener	Aluminum Complex
Color	White
Dropping Point, °C (°F)	>260 (>500)
Density, lbs/gal	8.58
Penetration, Worked (60 strokes), ASTM D217	265-295
Texture	Smooth, Adhesive
Copper Corrosion, ASTM D4048	1b
Four-Ball EP, ASTM D2596, Weld Point, kgf	500
Four-Ball Wear, ASTM D2266, Scar Diameter, mm	0.60
Oxidation Stability, ASTM D942, 100 hours,	
Pressure Drop, psi (kPa)	5 (35)
Rust Prevention, ASTM D1743	Pass
Timken OK Load, ASTM D2509, lb	40
Water Washout Resistance, ASTM D1264,	
Weight Loss @ 175°F, %	5
Base Oil Properties:	
Viscosity,	
cSt @ 40°C	220
cSt @ 100°C	18.5
SUS @ 100°F	1,165
SUS @ 210°F	95
Viscosity Index	100
Usable Temperature Range,	
°C	-29 to 149
°F	-20 to 300

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2009 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.