



## Hydroclear® TCS Slideway Lubricant

Conoco® Hydroclear TCS Slideway Lubricant is a premium, demulsible circulating oil developed for use on lathes and heavily loaded machine tool slideways. It is specially formulated to prevent stick-slip problems to ensure good surface finish on the machined part, and to provide quick and effective separation from water and metalworking fluids.

Hydroclear TCS Slideway Lubricant is specially formulated to allow machine tool carriages to start easily and move smoothly throughout their travel, thus preventing stick-slip problems. This reduces carriage chatter and ensures a smooth finish on the machined part. Mild extreme-pressure properties prevent scoring of the slideways during carriage travel. A tackiness additive improves adhesion and prevents the oil from being squeezed off the slideways. It also helps prevent the oil from being washed away by cutting fluids. Additional proprietary additives provide protection against rust and corrosion and allow optimum separation from coolants and tramp oils.

Hydroclear TCS Slideway Lubricant is water-white in color to allow easy visibility of machined parts.

### **Applications**

- Horizontal and vertical slideways on machine tools, such as lathes, planers, shapers, drilling machines, milling machines and screw machines
- Printing presses
- Lumber mill saw carriages
- Other applications that require a clear, tacky slideway oil

### **Features/Benefits**

- Excellent anti-stick-slip performance
- Excellent coolant-separating properties
- Good surface finish
- Protects against scoring and wear
- Good adhesion for retention on slideways
- Protects against rust and corrosion
- Water-white in color for easy visibility

**Premium  
Machine Tool  
Slideway  
Lubricant**

### **Contact Information**

**U.S. Customer  
Service:  
1-800-640-1956**

**Technical Hot Line:  
1-800-255-9556**

**International  
Customer Service:  
+1-832-486-3363  
+1-832-486-3870**

**E-mail address:  
*conocolubricants@  
conocophillips.com***

***<http://lubes.conoco.com>***

**600 N. Dairy Ashford • 2W9000 • Houston, TX 77079**



## Hydroclear® TCS Slideway Lubricant

### Typical Properties

ISO Grade	32	68	220
Specific Gravity @ 60°F	0.848	0.870	0.874
Density, lbs/gal @ 60°F	7.07	7.25	7.29
Color, ASTM D1500	0.0	0.0	0.0
Flash Point (COC), °C (°F)	205 (401)	232 (450)	280 (536)
Pour Point, °C (°F)	-15 (5)	-15 (5)	-12 (10)
Viscosity,			
cSt @ 40°C	32.0	69.0	227
cSt @ 100°C	6.1	9.0	23.8
SUS @ 100°F	164	357	1,184
SUS @ 210°F	46.6	56.6	118
Viscosity Index	141	104	130
Acid Number, ASTM D974, mg KOH/g	1.3	1.3	1.3
Demulsibility, ASTM D1401, minutes to pass	20	20	20
Rust Test, ASTM D665 A&B	Pass	Pass	Pass
Stick-Slip Performance, ASTM D2877	<0.8	<0.8	<0.8

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, Conoco, and the Conoco logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.