



SPECIFICATIONS and TECHNICAL DATA

Advanced Formula MOA[®]

PN 110



<u>TEST</u>	<u>ASTM TEST METHOD</u>	<u>TYPICAL TEST RESULTS</u>
API Gravity @ 60°F	D 287	19.7
Specific Gravity @ 60°F	D 1298	0.9358
Density, U.S. lbs./gal. @ 60°F	D 1250	7.802
Flash Point, °C (°F) COC	D 92	192 (378)
Viscosity, cSt @ 100°C (212°F)	D 445	11.18
Viscosity, cSt @ 40°C (104°F)	D 445	84.62
Viscosity Index	D 2270	120
Pour Point, °C (°F)	D 97	-8 (-22)

PROBLEM: Today's stop-and-go driving conditions and high ambient temperatures cause rapid depletion of critical oil additives. This leads to severe oxidation of the engine oil. Oxidation starts as heavy, black sludge in the crankcase, oil screens, oil passages, rocker arms and other critical areas of the engine.

SOLUTION: BG Advanced Formula MOA has been designed to fortify engine oil and extend its useful life. Its unique blend of additives maintains engine cleanliness and performance under the most difficult, high stress operating conditions. Can be used in gasoline or diesel engines.

This product is a part of the BG TDC[®] program.

- BENEFITS:**
- prevents oil thickening
 - prevents oil oxidation
 - prevents sludge and varnish deposits during stop-and-go driving
 - protection against rust and corrosion
 - provides greater power and performance
 - provides increased fuel mileage
 - reduces emissions

USAGE: Add one can of BG Advanced Formula MOA to crankcase with each oil change or anytime the oil level is low to fortify the engine oil. Do not overfill crankcase.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.