



# AMERICAN REFINING GROUP, INC.

## *PRIVATE LABEL & GENERIC LUBRICANTS*

### SPECIFICATION SHEET

**PRODUCT:** **R&O AW ISO VG 100 HYDRAULIC FLUID  
2000+ HOURS**

**PRODUCT CODE:** **H43-7384**

| ASTM<br>METHOD | SPECIFICATION           |  | TYPICAL |
|----------------|-------------------------|--|---------|
| D-4052         | GRAVITY, API            |  | 29.8    |
|                | LB/GAL                  |  | 7.319   |
| D-445          | VISCOSITY @ 40 °C, cSt  |  | 100.0   |
| D-445          | VISCOSITY @ 100 °C, cSt |  | 11.3    |
| D-2270         | VISCOSITY INDEX         |  | 95      |
| D-1500         | COLOR                   |  | 1.0     |
| D-5949         | POUR POINT °C           |  | -30     |
| D-92           | FLASH POINT °F          |  | 440     |
| D-6304         | KF MOISTURE, ppm (Max.) |  | 200     |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |
|                |                         |  |         |