



Product Data Sheet

AIR TOOL OIL

PREMIUM QUALITY AIR TOOL AND AIR LINE OIL

Feb 2011

Air Tool Oil is a highly refined oil, formulated to provide protection from rust, oxidation and wear and meet the operational requirements of reciprocating and rotary air tools, valves and cylinders.

In service **Air Tool Oil** offers the following benefits:

- ◆ Protection against rust and corrosion
- ◆ Enhanced Seal Conditioners
- ◆ Non-zinc, phosphorus anti-wear
- ◆ Low viscosity to aid in heat reduction

Product Applications

For satisfactory performance, air tool lubricants must lubricate the air tool, absorb and carry away moisture in the air supply and maintain 'O' Ring dimensional stability. **Air Tool Oil** is specifically formulated to perform these functions and contribute to improved tool performance, fewer parts replacements and improved productivity. **Air Tool Oil** can also be used in some hydraulic systems calling for an ISO 22 product.

Product Maintenance and Handling

Air Tool Oil is manufactured from high quality petroleum base stocks carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to the Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

Typical Properties

	Air Tool Oil
ISO Viscosity Grade	22
Density @15°C, kg/m ³	860
Pour Point, °C	-38
Flash Point, °C	169
Viscosity Index	101
Kinematic Viscosity, cSt	
@ 40°C	20.9
@ 100°C	4.2
Rust Test, Sea Water	Pass

The typical properties shown above are representative of current production. Some are controlled by manufacturing and performance specifications while others are not. All may vary within modest ranges.