



Product Specification and Technical Data

PRODUCT: BG Premium Lubricating Grease w/ RF-7

PART NO.: 600



NLGI DATA: NLGI Grade: 2 Color: Red Thickeners Type: Lithium 12 hydroxy stearate
NLGI Rating: LB Texture: Smooth/Tacky

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	Worked Penetration @ 25°C (77°F), 60 Strokes	D 217	280
	Dropping Point, min.	D 2265	202°C (395°F)
	Rust Prevention Rating	D 1743	Pass
	Water Washout	D 1264	3.8%
	Timken, OK Load, LB	D 2509	45
	Four Ball EP		
	Weld Pt. Kg	D 2596	250
	LWI	D 2596	48
	Base Oil		
	Viscosity, cSt @ 100°C (212°F).	D 445	29.2
	Viscosity, cSt @ 40°C (104°F)	D 445	322
	Viscosity Index	D 2270	124
	Oxidation Stability, LB Loss/100 hrs	D 942	2 (5 max)

DESCRIPTION BG Premium Lubricating Grease is formulated with outstanding “water shed” capabilities and is capable of enduring shock and pounding in applications such as bucket pins, rock crushers, pile drivers and under adverse conditions of load and torque. Highly suited for use in plain and anti-friction bearings where extremely high operating temperatures are not encountered.

An all-season, multi-purpose, lithium-base grease, BG Premium Lubricating Grease is specially formulated with RF-7 to provide the toughest lubricant film possible under a wide variety of conditions. It has unusual cohesive and adhesive properties for retention in bearings and on metal surfaces. Special extreme pressure ingredients give it excellent load carrying capabilities.

BG Premium Lubricating Grease combines excellent shear stability, oxidation stability and high fluid viscosity to provide outstanding heavy duty lubricating capabilities. It also offers good low temperature pumpability.

BG Premium Lubricating Grease is a multi-purpose grease recommended for automotive, industrial, commercial and farm applications.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.