



SUPER MOTOR OIL Synthetic Blend

SUPER MOTOR OIL SAE 0W-20, 5W-20 and 5W-30 are Synthetic Blend Passenger Car Motor Oils engineered to meet the most demanding lubrication requirements of modern gasoline fuelled engines. Formulated with advanced additives and premium quality base stocks, Super Motor Oil protects engines against undesirable deposits, oxidation, and viscosity and thermal breakdown. SAE 0W-20, 5W-20 and 5W-30 are Resource Conserving, meeting API service SN and ILSAC GF-5, as well as older categories: API SM, SL and previous ILSAC categories.

TYPICAL CHARACTERISTICS

	METHOD		0W-20	5W-20	5W-30
Viscosity @ 40 °C	D445	cSt	43.5	49.7	61.6
Viscosity @ 100 °C	D445	cSt	8.3	8.6	10.4
Viscosity Index	D2270		170	150	158
CCS Viscosity	D5293	cP	5250@-35°C	6000 @-30°C	6200 @-30°C
Pour Point	D97	°C	-45	-39	-39
Flash Point	D92	°C	200	216	220
Evaporative Loss, NOACK, wt%	D5800		13	<15	<15
Specific Gravity 15°C	D4052		0.849	0.862	0.861
Zinc (ppm)	D4951		850	850	850
Phosphorus (ppm)	D4951		700	700	700

PROPERTIES AND PERFORMANCE

- API SN
- ILSAC GF-5
- Resource Conserving

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.

Eni USA R&M Co. Inc.

Pennsylvania–Ohio–West Virginia 1-800-922-9243
New Jersey 1-800-543-9556
New York 1-800-632-8777
Canada 1-800-957-2447

Rev. 1/30/12
Supersedes 2/1/11

Page 1 of 1