



Special Limited-Slip Gear Lubricant

Kendall Special Limited-Slip Gear Lubricant is an extreme-pressure, API GL-5, SAE 80W-90 automotive gear oil specially formulated to satisfy the lubrication needs of most limited-slip rear axles. It is friction-modified to help eliminate the stick-slip chatter associated with low-speed, high-torque operation of limited-slip differentials while turning corners with some passenger cars and light trucks.

Special Limited-Slip Gear Lubricant is formulated to provide long service life and extended gear life in automotive differentials operating under varying conditions of speed, load, temperature and torque. The carefully balanced formulation is designed to minimize oxidative sludge and varnish formation, reduce wear, prevent scoring damage, and protect against metal fatigue under shock-load conditions.

Applications

Special Limited-Slip Gear Lubricant will provide excellent protection in passenger car and truck axles with either conventional or limited-slip differentials. It may be used for initial fill of new or rebuilt limited-slip differentials, for top-off and for refill after a complete drain.

Special Limited-Slip Gear Lubricant meets or exceeds the requirements of:

- API Service GL-5
- Ford WSP-M2C197-A
- MIL-PRF-2105E
- SAE J2360

Features/Benefits

- Excellent oxidation resistance and thermal stability to minimize sludge and varnish formation
- Excellent thermal durability and extreme-pressure properties for extended gear life
- High load-carrying capacity for protection against scuffing and wear
- Protects against rust and corrosion
- Good foam resistance
- Friction-modified to prevent chatter in limited-slip and positraction differentials

**Friction-Modified
Automotive
Gear Lubricant,
API GL-5**

**Customer Service
Number:
1-800-368-7128**

**Technical Hot Line:
1-800-368-1267**

**E-mail address:
*kendallmotoroil@
conocophillips.com***

www.kendallmotoroil.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

Note: The oil-soluble friction modifier in this product is available in 4-oz. plastic bottles as Kendall Limited-Slip Axle Additive Concentrate. This concentrate may be used to modify the frictional characteristics of conventional API GL-5 gear lubricants to meet the lubrication needs of limited-slip differentials.

Special Limited-Slip Gear Lubricant

Typical Properties

SAE Grade	80W-90
Density, g/cm ³ @ 15.6°C (60°F)	0.890
Density, lbs/gal @ 15.6°C (60°F)	7.41
Color, ASTM D1500	3.0
Flash Point (COC), °C (°F)	207 (405)
Pour Point, °C (°F)	-33 (-27)
Viscosity,	
cP @ -26°C (Brookfield)	120,000
cSt @ 40°C	161
cSt @ 100°C	15.9
SUS @ 100°F	845
SUS @ 210°F	83.4
Viscosity Index	102

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2007 ConocoPhillips Company. The ConocoPhillips logo, Kendall and the Kendall logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.