



SUPER LUBE® GREASE NLGI 0

SUPER LUBE® GREASE NLGI 0

Super Lube® Grease is a patented synthetic NLGI grade 0 heavy-duty, multipurpose lubricant with PTFE. Synthetic base fluids and the addition of PTFE micro powders combine to form a premium lubricant that provides longer life protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced, and productivity is increased.

Super Lube® Grease is a USDA listed Food Grade lubricant, rated H-1 for incidental food contact.

Super Lube® Grease will not run or drip, does not evaporate or form gummy deposits and will not melt or separate.

Super Lube® Grease is a synthetic, heavy-duty lubricant that is compatible with most other lubricants.

Super Lube® Grease outlasts conventional greases 50-100% and has excellent adhesion.

Super Lube® Grease controls as well as reduces bacterial growth with a revolutionary antimicrobial and bacterial reduction additive package.



Part No.	Description
41150/0	400 gr Cartridge
41160/0	400 gr Can
41050/0	5 lb Pail
41030/0	30 lb Pail
41120/0	120 lb Keg
41140/0	400 lb Drum



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com



**Super
Lube®**



SUPER LUBE® GREASE

SUPER LUBE® GREASE

Super Lube® Grease Typical Applications:

- ▶ Plain, anti-friction, ball, roller, wheel bearings
- ▶ Cams, slides, valves, conveyors, chains
- ▶ Food processing equipment
- ▶ Caliper assembly and bearing grease
- ▶ Hubs, axles, chassis, shocks, springs
- ▶ Seat regulators and tracks
- ▶ Fifth wheels
- ▶ Parts lubricant
- ▶ Winches, pulleys, snaps
- ▶ Trailer and buddy bearings
- ▶ Dielectric grease, battery protector
- ▶ Campers, trailers, bicycles, guns, fishing gear, motorcycles, hunting gear
- ▶ Weight and fitness equipment
- ▶ Linkages, hinges and locks
- ▶ Lawn movers, garage doors, snow blowers, sewing machines
- ▶ Faucets and pool pumps
- ▶ Garden and farm equipment

Benefits:

- ▶ Clean, non-toxic, non-staining
- ▶ Dielectric
- ▶ USDA Rating H-1
- ▶ Contains a revolutionary antimicrobial and bacterial reduction additive package
- ▶ Will not drip, run or evaporate
- ▶ Impervious to salt water, safe in potable water
- ▶ Long lasting
- ▶ Prevents rust and corrosion while reducing friction
- ▶ Wide Temperature Range -45° to 450°F



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com





SUPER LUBE® GREASE

SUPER LUBE® GREASE

Typical Properties		
Test	Test Method	Rating
Color		Translucent White
NLGI Grade	ASTM D1092	0
Dropping Point	ASTM D566	>500°F (206°C)
Four Ball test:	ASTM D2783	
Load wear index		81.73 kg
Weld Point		400 kg
Oxidation Stability 100 hrs	ASTM D942	0 psi
Wheel bearing Leakage	ASTM D1263	0.2 g
Copper Corrosion 24 hrs @ 100°C	ASTM D4048	1B, shiny
Shelf Life		24 months

While the information contained herein is believed to be reliable, Synco Chemical Corporation Chemical Corporation makes no representation as to the reliability of the results the buyer or user will achieve.



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com

