



El Mar[®] Mid Ash Supreme

Conoco[®] El Mar Mid Ash Supreme is a premium quality, mid-ash, dispersant-detergent gas engine oil designed for use in naturally aspirated and moderately to highly turbocharged 4-stroke cycle natural gas engines. It is particularly recommended for use in natural gas engines and dual-fuel engines burning sour gas or landfill gas.

El Mar Mid Ash Supreme is formulated with field-proven performance additives to provide excellent resistance to oxidation and nitration, protect against piston scuffing and wear, and minimize the formation of sludge and piston deposits for good engine cleanliness. It has a high alkaline reserve (TBN) to protect engines operating under corrosive conditions, such as when burning sour gas, digester gas or landfill gas.

El Mar Mid Ash Supreme is designed specifically for use in Waukesha gas engines, and has extensive field experience in Waukesha VHP GL turbocharged lean-burn engines. It also is recommended for use in other 4-stroke cycle natural gas engines that require a mid-ash gas engine oil containing 1 percent (nominal) sulfated ash.

Applications

- 4-stroke cycle gas and dual-fuel engines burning sour gas or landfill gas
- 4-stroke cycle gas engines in wastewater treatment plants fueled by digester gas
- 4-stroke cycle converted irrigation engines running on natural gas or LPG
- Other 4-stroke cycle natural gas engines where the manufacturer specifies a mid-ash gas engine oil

El Mar Mid Ash Supreme is recommended for use in natural gas engines manufactured by:

- Colt-Fairbanks Morse
- Cooper Superior
- Nordberg
- Waukesha (VHP GL turbocharged, lean-burn engines, models 3521, 5115, 7042, 9390)

**Premium Mid-Ash
Natural Gas
Engine Oil**

**U.S. Technical
Services Hot Line:
1-800-255-9556**

**U.S. Customer
Service:
1-800-640-1956**

**International:
+1-832-486-3363**

**E-mail address:
*conocolubricants@
conocophillips.com***

<http://lubes.conoco.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Features/Benefits

- Excellent resistance to oxidation and nitration
- High alkaline reserve to combat acidic combustion by-products when burning sour gas
- High dispersancy protects against sludge and varnish formation
- Protects against scuffing and wear
- Protects against rust and corrosion
- Compatible with emissions system catalysts
- Does not contain any bright stock, which can cause harmful carbon deposits

El Mar® Mid Ash Supreme

Typical Properties

SAE Grade	30	40	15W-40
Specific Gravity @ 60°F	0.881	0.884	0.875
Density, lbs/gal @ 60°F	7.35	7.37	7.30
Color, ASTM D1500	7.5	7.5	7.5
Flash Point (COC), °C (°F)	238 (460)	263 (505)	232 (450)
Pour Point, °C (°F)	-33 (-27)	-33 (-27)	-39 (-38)
Viscosity, Kinematic			
cSt @ 40°C	91.0	132	109
cSt @ 100°C	10.8	13.8	14.3
Viscosity Index	104	101	133
Cold Cranking Viscosity, cP	—	—	6,550
@ (°C)	—	—	(-20)
Sulfated Ash, ASTM D874, wt %	1.0	1.0	1.0
Total Base Number (TBN), ASTM D2896	8.2	8.2	8.2
Phosphorus, wt %	0.028	0.028	0.028
Zinc, wt %	0.032	0.032	0.032

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, Conoco, and the Conoco logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.