



Product Specification and Technical Data

PRODUCT: BG Chain Lubricant for Farm and Industry

PART NO.: 495F

TEST DATA: Test	ASTM Test Method	Typical Test Results
API Gravity @ 15.6°C (60°F)	D 287	27.9
Specific Gravity @ 15.6°C (60°F).	D 1298	0.8876
Density, U.S. lbs./gal. @ 15.6°C (60°F)	D 1250	7.4
Flash Point, COC	D 92	260°C (500°F)
Viscosity, cSt @ 100°C (212°F)	D 445	14.37
Viscosity, cSt @ 40°C (104°F).	D 445	132.85
Viscosity Index	D 2270	107
Pour Point	D 97	-12°C (10°F)
Color	Visual.	Grey/Black
Net Weight, oz. (grams)		15 (425)
Volume, fl. oz.		13.44

DESCRIPTION: BG Chain Lubricant for Farm and Industry was developed specifically for roller chain lubrication. It is highly adhesive to metal surfaces. Contains Moly for added lubrication. Resistant to water washout. BG Chain Lubricant for Farm and Industry will not cause deterioration of chain components. Recommended for chains, slides and all applications where an adhesive oil lubricant is required.

For best results, chain should be clean and dry before applying BG Chain Lubricant for Farm and Industry. Apply lubricant to the inside of the chain, making sure to lubricate each chain roller.

This product is available in aerosol and liquid form.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.