Revision #:2 Page **1** of **7**

Material Safety Data Sheet

Prepared according to 29 CFR 1910.1200

Chemical Product and Company Identification

American Refining Group, Inc. 77 North Kendall Avenue Bradford, PA 16701 USA

Tel: (814) 368.1200 www.amref.com



Product Name Brad Penn® Penn-Grade 1TM V2 SAE 10W-40 4-Stroke Motorcycle

Oil

Product Code BP7156

CAS Number Not applicable for mixtures

Petroleum distillate **Generic Chemical Name**

Product Type Mixture

Transportation Emergency Phone No. Chemtrec: 1-800-424-9300 (24 HRS)

ARG Emergency Phone No. 814-368-1297 (24 HRS) **MSDS E-Mail** msds@amref.com

2. Hazards Identification

Liquid **Appearance**

Petroleum Oil Odor Signal Word WARNING!

> Harmful if inhaled May cause skin irritation May cause eye irritation

May cause respiratory tract irritation

This material is considered hazardous by the OSHA Hazard **OSHA Regulatory Status**

Communication Standard (29 CFR 1910.1200)

Precautions

Inhalation Avoid breathing dust/fume/gas/mist/vapors/spray. Keep container

tightly closed. Use only with adequate ventilation.

Avoid contact with eyes. Wash thoroughly after handling. **Eves** Avoid contact with skin and clothing. Wash thoroughly after Skin

handling.

Medical Conditions Aggravated by

Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this **Exposure**

product

Chronic Effects See Section 11 for complete health hazard information See Section 12 for complete ecological information **Environmental Effects**

Composition / Information on Ingredients

Page 2 of 7

Revision #:2

3. Composition / Information on Ingredients			
CAS No. Component Percent			
64742-54-7	Petroleum distillates, hydrotreated heavy paraffinic	35-45	
64742-01-4	Residual oils (petroleum), solvent refined	1-5	

Component Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Mineral Oil (See Section 8)

4. First Aid Measures			
Eyes	Check for and remove any contact lenses. Immediately flush eyes		
•	with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.		
Skin	In case of contact, immediately flush skin with plenty of water for at		
	least 15 minutes while removing contaminated clothing and shoes.		
	Wash clothing before reuse. Clean shoes thoroughly before reuse.		
	Get medical attention immediately.		
Inhalation	Move exposed person to fresh air. If not breathing, if breathing is		
	irregular or if respiratory arrest occurs, provide artificial respiration		
	or oxygen by trained personnel. Loosen tight clothing such as a		
T	collar, tie, belt or waistband. Get medical attention immediately.		
Ingestion	DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water. Get medical attention immediately.		
Note to Physicians	No specific treatment. Treat symptomatically. Contact poison		
1 (ote to 1 my stellins	treatment specialist immediately if large quantities have been		
	ingested or inhaled.		
	5. Fire Fighting Measures		

Flammable Properties

Not available

Extinguishing Media

Use dry chemical, CO₂, water spray (FOG) or foam

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposition products may include the following materials: Carbon dioxide and Carbon monoxide.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas.

Revision #:2 Page **3** of **7**

6. Accidental Release Measures

Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution.

Methods for Containment

Stop leak if without risk.

Methods for Cleanup

Move containers from spill area. Approach release from upwind. Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and Storage

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

Shipping and Storing Procedures

Store in accordance with local regulations. Store in a segregated and approved area. Keep in the original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Do not store in unlabeled containers. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers that retain product residue may be hazardous. Do not reuse container.

8. Exposure Controls / Personal Protection

Component Exposure Limits

Oil Mist (mineral)

ACGIH TLV: TWA: TWA: 5 mg/m^3 STEL: 10 mg/m^3 N/A ppm N/A ppm STEL: N/A mg/m³ N/A ppm 5 mg/m^3 STEL: N/A ppm OSHA PEL: TWA: TWA STEL: 10 mg/m^3 5 mg/m^3 NIOSH REL: TWA: N/A ppm TWA STEL: N/A ppm STEL:

N/A signifies not available

Engineering Controls Material should be handled in enclosed vessels and equipment. Use

> only in adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Chemical goggles or face shield. **Eye/Face Protection** Skin Protection

Chemical resistant, impervious gloves complying with an approved standard should be worn at all times. Coveralls, apron, and boots as

necessary to minimize contact.

Use a properly fitted, air-purifying or air-fed respirator complying with **Respiratory Protection**

an approved standard if a risk assessment indicated this is necessary.

Revision #:2 Page 4 of 7

8. Exposure Controls / Personal Protection

Respirator selection must be based on known or anticipated exposure

levels.

General Hygiene Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove

potentially contaminated clothing.

9. Physical and Chemical Properties

Appearance	Green	Vapor Pressure (mm Hg	0
		at 20 °C)	
Odor	Petroleum Oil	Water Soluble	No
Physical State	Liquid	Specific Gravity (g/cc)	.86
Flash Point (T)	425	Density (lbs/gal)	7.2
Boiling Point (T)	>625	pН	Not available

10. Chemical Stability & Reactivity Information

Stability Stable under normal conditions

Polymerization No polymerization

Incompatibility Strong acids and oxidizing materials

Conditions to Avoid High temperatures

Hazardous Decomposition

Products

Smoke, carbon monoxide, carbon dioxide, aldehydes and other products

of incomplete combustion.

11. Toxicological Information

Acute Exposure

Respiratory Irritation Inhalation hazard. If material is misted or if vapors are generated from heating,

exposure may cause irritation of mucous membranes and the upper respiratory

tract.

Eye Irritation May cause eye irritation. Vapors formed from heating may cause eye irritation.

Skin Irritation May cause skin irritation. Prolonged or repeated direct exposure to the skin

may result in symptoms of irritation and redness, dermatitis or oil acne.

Sensitization Not expected to cause skin or respiratory sensitization.

Component Analysis – LD50 / LC50

Acute Toxicity Estimate (ATE) Values for Product:

 Inhalation LC50 Rat
 18* mg/L 1 HR

 Oral LD50 Rat
 >4500 mg/kg

 Dermal LD50 Rabbit
 >2000 mg/kg

^{*8.2%} of the mixture's LC50 is unknown

BRAD PENN® PENN-GRADE 1™ V2 SAE 10W-40 4-STROKE MOTORCYCLE OIL BP7156

American Refining Group, Inc.

Revision #:2 Page **5** of **7**

Chronic Exposure

Target Organ Effects No data available to indicate product or components present at greater than 1%

are chronic health hazards.

Carcinogenicity This product contains mineral oils which are considered to be severely refined

and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP

346 or Modified Ames test.

Mutagenicity No data available to indicate product or any components present at greater than

.1% are mutagenic or genotoxic.

Reproductive ToxicityNo data available to indicate product or any components present at greater than

.1% are a reproductive toxin.

Teratogenicity No data available to indicate product or any components contained at greater

than .1% may cause birth defects.

12. Ecological Information

Component Analysis- Ecotoxicity - Aquatic Life

Duration/Test/Species Concentration/Conditions

96 Hr LC50 N/A mg/L Pimephales promelas

DegradabilityNot determinedBioaccumulationNot determinedSoil MobilityNot determined

13. Disposal Considerations

Disposal Instructions

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

14. Transportation Information

Emergency Response Guide No. 128 North American Emergency Response

Guide Book

UN Number Shipping Name (technical name) Hazard Class Packing Group

U.S. DOT Not Regulated

Bulk

U.S. DOT Not Regulated

Non-Bulk

15. Regulatory Information

Revision #:2 Page 6 of 7

13	5.	Keg	gula	tory	Info	rmai	110	n	
		- 1							Τ

SARA Extremely Hazardous Substances (Sections 302 & 304) This product does not contain greater than 1% of any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B. This product does not contain greater than 1.0% of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR

SARA Section 313

Part 372.

SARA Section 311 & 312 Classifications

Acute Hazard Yes
Chronic Hazard No
Fire Hazard No
Reactivity Hazard No

CERCLA

This product does not contain any "hazardous substances" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

California Prop 65

This product contains chemical(s) known to the state of California to cause

cancer and/or birth defects.

Clean Water Act / Oil

Pollution Act

This product contains petroleum distillates and may be subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National

Response Center at 1-800-424-8802.

Global Chemical Inventories

Inventory	Component	
	All components	
US TSCA	Present	
EU	Not available	
Japan	Not available	
Australia	Present	
New Zealand	Not available	
Canada	Not available	
Switzerland	Not available	
Korea	Not available	
Philippines	Present	
China	Not available	
Taiwan	Not available	

16. Other Information

US NFPA Ratings

Health	Fire	Instability
1	1	0

Revision #:2 Page **7** of **7**

16. Other Information			
Health Fire Physical Hazards			
1	1	0	

Precautionary Labels

Signal Word WARNING!

Harmful if inhaled

May cause skin irritation May cause eye irritation

May cause respiratory tract irritation

Preparation/Revision Date 5/23/2012

Revision Reason Outdated MSDS

Prepared By: Katie Vecellio, EHS Intern

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS