Material Safety Data Sheet

Prepared according to 29 CFR 1910.1200

1. Chemical Product and Company Identification

American Refining Group, Inc. 77 North Kendall Avenue Bradford, PA 16701 USA

Tel: (814) 368.1200 www.amref.com



Product Name

Brad Penn® Low Pour Universal 2 Stroke Engine Oil TC-W3 SAE

20W-30

Product Code BP7253

CAS Number Not applicable for mixtures

Synonyms 2 Stroke Oil

Generic Chemical Name Petroleum distillate

Product Type Mixture

Transportation Emergency Phone No. Chemtrec: 1-800-424-9300 (24 HRS)

ARG Emergency Phone No. 814-368-1297 (24 HRS)
MSDS E-Mail msds@amref.com

2. Hazards Identification

AppearanceGreen liquidOdorSolventSignal WordWARNING!

Combustible liquid and vapor

Harmful if inhaled

Prolonged or repeated skin contact may cause irritation

May cause skin irritation May cause eye irritation

May cause respiratory tract irritation

May cause chronic effects

Target Organ: Central nervous system

Exposure Routes Inhalation, ingestion, skin and/or eye contact

Precautions Keep away from heat, sparks and flame. Keep container tightly

closed. Use only with adequate ventilation.

Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.

Inhalation Avoid breathing dust/fume/gas/mist/vapors/spray. Keep container

tightly closed. Use only with adequate ventilation.

Eyes Avoid contact with eyes. Wash thoroughly after handling. **Skin** Avoid contact with skin and clothing. Wash thoroughly after

handling.

Medical Conditions Aggravated by Pre-existing disorders involving any target organs mentioned in this

2. Hazards Identification		
Exposure	MSDS as being at risk may be aggravated by over-exposure to this	
	product	
Chronic Effects	See Section 11 for complete health hazard information	
Environmental Effects	See Section 12 for complete ecological information	

3. Composition / Information on Ingredients

CAS No.	Component	Percent
64741-88-4	Petroleum distillates, solvent-refined heavy paraffinic	20-30
64742-54-7	Hydrotreated heavy paraffinic distillate	20-30
64742-01-4	Residual oils (petroleum), solvent refined	10-20
64742-47-8	Petroleum distillates, hydrotreated light	20-30
64742-94-5	Petroleum naphtha	0-1.5

Component Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Mineral oil (mist) (See Section 8)

4. First Aid Measures		
Eyes	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the	
Skin	upper and lower eyelids. Get medical attention immediately. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.	
	Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.	
Inhalation	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.	
Ingestion	DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water. Get medical attention immediately.	
Note to Physicians	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	

5. Fire Fighting Measures

Flammable Properties

Combustible liquid. Avoid heat and flame.

Extinguishing Media

5. Fire Fighting Measures

Use dry chemical, CO₂, water spray (FOG) or foam

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposition products may include the following materials: Carbon dioxide and Carbon monoxide.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution.

Methods for Containment

Stop leak if without risk.

Methods for Cleanup

Move containers from spill area. Approach release from upwind. Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and Storage

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

Shipping and Storing Procedures

Store in accordance with local regulations. Store in a segregated and approved area. Keep in the original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Do not store in unlabeled containers. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers that retain product residue may be hazardous. Do not reuse container.

8. Exposure Controls / Personal Protection

Component Exposure Limits

Mineral Oil (mist)

 5 mg/m^3 10 mg/m^3 **ACGIHTLV:** TWA: N/A ppm TWA: STEL: N/A ppm STEL: 5 mg/m^3 N/A mg/m³ N/A ppm TWA STEL: N/A ppm STEL: **OSHA PEL:** TWA: 5 mg/m^3 10 mg/m^3 NIOSH REL: TWA: N/A ppm TWA STEL: N/A ppm STEL:

N/A signifies not available

8. Exposure Controls / Personal Protection	
This product is a combustible liquid. Material should be handled in	
enclosed vessels and equipment. Use only in adequate ventilation. Use	
process enclosures, local exhaust ventilation or other engineering	
controls to keep worker exposure to airborne contaminants below any	
recommended or statutory limits.	
Chemical goggles or face shield.	
Chemical resistant, impervious gloves complying with an approved	
standard should be worn at all times. Coveralls, apron, and boots as	
necessary to minimize contact.	
Use a properly fitted, air-purifying or air-fed respirator complying with	
an approved standard if a risk assessment indicated this is necessary.	
Respirator selection must be based on known or anticipated exposure	
levels.	
Wash hands, forearms and face thoroughly after handling chemical	
products, before eating, smoking and using the lavatory and at the end of	
the working period. Appropriate techniques should be used to remove	
potentially contaminated clothing.	

9. Physical and Chemical Properties

Appearance	Green	Vapor Pressure (mm Hg	.20
		at 20 °C)	
Odor	Solvent	Water Soluble	No
Physical State	Liquid	Specific Gravity (g/cc)	.86
Flash Point (T)	150	Density (lbs/gal)	7.2
Boiling Point (°F)	>365	pH	Not available

10. Chemical Stability & Reactivity Information

Stability Stable under normal conditions.

Polymerization No polymerization

IncompatibilityStrong acids and oxidizing materialsConditions to AvoidHigh temperatures, sparks, flames

Hazardous Decomposition Smoke, carbon monoxide, carbon dioxide, aldehydes and other products

Products of incomplete combustion.

11. Toxicological Information

Acute Exposure

Respiratory Irritation Inhalation hazard. If material is misted or if vapors are generated from heating,

exposure may cause irritation of mucous membranes and the upper respiratory

tract. Based on data from components or similar materials.

Eye Irritation May cause eye irritation. Weak to moderate eye irritant. Vapors formed from

heating may cause eye irritation.

Skin Irritation Can cause skin irritation. Prolonged or repeated direct exposure to the skin

11. Toxicological Information

results in symptoms of irritation and redness, dermatitis or oil acne.

Sensitization Not expected to cause skin or respiratory sensitization.

Component Analysis – LD50 / LC50

Acute Toxicity Estimate (ATE) Values for Product:

 Inhalation LC50 Rat
 15.36* mg/L 1 HR

 Oral LD50 Rat
 >5400 mg/kg

 Dermal LD50 Rabbit
 2100-3600 mg/kg

Chronic Exposure

Target Organ Effects Repeated overexposure to petroleum naphtha can cause central nervous

damage.

Carcinogenicity This product contains mineral oils which are considered to be severely refined

and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to produce negative results via the Modified

Ames test.

Mutagenicity No data available to indicate product or any components present at greater than

.1% are mutagenic or genotoxic.

Reproductive Toxicity No data available to indicate either product or components present at greater

than .1% that may cause reproductive toxicity.

Teratogenicity No data available to indicate product or any components contained at greater

than .1% may cause birth defects.

12. Ecological Information

Component Analysis- Ecotoxicity – Aquatic Life

Duration/Test/Species Concentration/Conditions

96 Hr LC50 N/A mg/L

Pimephales promelas

DegradabilityNot determinedBioaccumulationNot determinedSoil MobilityNot determined

13. Disposal Considerations

Disposal Instructions

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

14. Transportation Information

^{*15%} of mixture's LC50 Inhalation is unknown

14. Transportation Information

Emergency Response 128 North American Emergency Response Guide Book Guide No. UN Shipping Name (technical **Hazard Class Packing Group** Labels/Placard* Number name) Petroleum Distillates. U.S. DOT 1268 combustible Ш **Bulk** N.O.S. (light distillate) liquid (over 119 gallons)

Bulk container must be labeled

on two

opposing sides Exempt from labeling and

unless shipped via Air or

placarding

Vessel

15. Regulatory Information

SARA Extremely Hazardous

This product does not contain greater than 1% of any "extremely hazardous substances" listed pursuant to Title III of the Superfund

Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B. This product does not contain greater than 1.0% of the substances

subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR

Part 372.

SARA Section 311 & 312 Classifications Acute Hazard Yes

Not Regulated

Chronic Hazard Yes **Fire Hazard** Yes **Reactivity Hazard** No

CERCLA This product does not contain any "hazardous substances" listed under the

Comprehensive Environmental Response, Compensation and Liability Act of

1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

California Prop 65 This product contains chemical(s) known to the state of California to cause

cancer and/or birth defects.

Clean Water Act / Oil

Pollution Act

SARA Section 313

U.S. DOT

Non-Bulk

(under 119

gallons)

This product may be subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to

surface waters must be reported to the National Response Center at 1-800-424-

8802.

^{*}Truck/Rail car must be placarded on 4 sides if aggregate gross weight exceeds 1,000 pounds

Global Chemical Inventories

Inventory	Component
	All components
US TSCA	Present
EU	Present
Japan	Not available
Australia	Present
New Zealand	Present
Canada	Present
Switzerland	Not available
Korea	Present
Philippines	Present
China	Not available
Taiwan	Not available

16. Other Information

US NFPA Ratings

Health	Fire	Instability
1	2	0

HMIS Ratings

Health	Fire	Physical Hazards
1*	2	0

Precautionary Labels

Signal Word WARNING!

Combustible liquid and vapor

Harmful if inhaled

Prolonged or repeated skin contact may cause irritation

May cause skin irritation May cause eye irritation

May cause respiratory tract irritation

May cause chronic effects

Target Organ: Central nervous system

Preparation/Revision Date 6/28/2012

Revision ReasonSection 11: Toxicological Information
Section 14: Transportation Information

Prepared By: Jenna Prechtl, Product Compliance Coordinator

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS