Revision #:4 Page **1** of **7**

Material Safety Data Sheet

Prepared according to 29 CFR 1910.1200

Chemical Product and Company Identification

American Refining Group, Inc. 77 North Kendall Avenue Bradford, PA 16701 USA

Tel: (814) 368.1200 www.amref.com



Brad Penn® Penn-Grade TM High VI R&O AW ISO VG 15 **Product Name**

Hydraulic Oil-Blue

Product Code BP7357

CAS Number Not applicable for mixtures

Petroleum distillate **Generic Chemical Name**

Product Type Mixture

Transportation Emergency Phone No. Chemtrec: 1-800-424-9300 (24 HRS)

ARG Emergency Phone No. 814-368-1297 (24 HRS) **MSDS E-Mail** msds@amref.com

2. Hazards Identification

Blue Liquid **Appearance** Petroleum Oil Odor Signal Word WARNING!

Harmful if swallowed. Can enter lungs and cause damage.

May cause skin irritation May cause eye irritation

May cause respiratory tract irritation

This material is NOT considered hazardous by the OSHA Hazard **OSHA Regulatory Status**

Communication Standard (29 CFR 1910.1200)

Precautions

Inhalation Avoid breathing dust/fume/gas/mist/vapors/spray. Keep container

tightly closed. Use only with adequate ventilation.

Avoid contact with eyes. Wash thoroughly after handling. **Eves** Avoid contact with skin and clothing. Wash thoroughly after Skin

handling.

Medical Conditions Aggravated by

Pre-existing disorders involving any target organs mentioned in this **Exposure**

MSDS as being at risk may be aggravated by over-exposure to this

product

Chronic Effects See Section 11 for complete health hazard information See Section 12 for complete ecological information **Environmental Effects**

Composition / Information on Ingredients

Page **2** of **7**

Revision #:4

3. Composition / Information on Ingredients		
CAS No.	Component	Percent
Mixture	Mixture of severely hydrotreated & hydrocracked base oil (petroleum)	75-85
64742-54-7	Petroleum distillates, hydrotreated heavy paraffinic	5-15

Component Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Mineral Oil (See Section 8)

4. First Aid Measures		
Eyes	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the	
Skin	upper and lower eyelids. Get medical attention immediately. In case of contact, immediately flush skin with plenty of water for at	
	least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.	
Inhalation	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.	
Ingestion	DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water. Get medical attention immediately.	
Note to Physicians	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	
	5. Fire Fighting Measures	

Flammable Properties

Not available

Extinguishing Media

Use dry chemical, CO₂, water spray (FOG) or foam

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposition products may include the following materials: Carbon dioxide and Carbon monoxide.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions

Revision #:4

Page **3** of **7**

6. Accidental Release Measures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution.

Methods for Containment

Stop leak if without risk.

Methods for Cleanup

Move containers from spill area. Approach release from upwind. Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and Storage

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

Shipping and Storing Procedures

Store in accordance with local regulations. Store in a segregated and approved area. Keep in the original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Do not store in unlabeled containers. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers that retain product residue may be hazardous. Do not reuse container.

8. Exposure Controls / Personal Protection

Component Exposure Limits

Oil Mist (mineral)

 5 mg/m^3 10 mg/m^3 **ACGIH TLV:** TWA: N/A ppm TWA: STEL: N/A ppm STEL: 5 mg/m^3 N/A mg/m³ **OSHA PEL:** TWA: N/A ppm TWA STEL: N/A ppm STEL: 5 mg/m^3 10 mg/m^3 N/A ppm TWA STEL: N/A ppm **NIOSH REL:** TWA: STEL:

N/A signifies not available

Eye/Face Protection

Engineering Controls Material should be handled in enclosed vessels and equipment. Use

> only in adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to

airborne contaminants below any recommended or statutory limits.

Chemical goggles or face shield.

Chemical resistant, impervious gloves complying with an approved **Skin Protection**

standard should be worn at all times. Coveralls, apron, and boots as

necessary to minimize contact.

Use a properly fitted, air-purifying or air-fed respirator complying with **Respiratory Protection**

Revision #:4 Page **4** of **7**

8. Exposure Controls / Personal Protection

an approved standard if a risk assessment indicated this is necessary. Respirator selection must be based on known or anticipated exposure

levels.

Wash hands, forearms and face thoroughly after handling chemical **General Hygiene**

> products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove

potentially contaminated clothing.

Physical and Chemical Properties

Color	Blue	Vapor Pressure (mm Hg	0
		at 20°C)	
Odor	Petroleum Oil	Water Soluble	No
Physical State	Liquid	Specific Gravity (g/cc)	.8468
Flash Point (T)	325	Density (lbs/gal)	7.051
Boiling Point (T)	>625	pН	Not available

10. Chemical Stability & Reactivity Information

Stability Stable under normal conditions

Polymerization No polymerization

Strong acids and oxidizing materials **Incompatibility**

Conditions to Avoid High temperatures

Hazardous Decomposition Smoke, carbon monoxide, carbon dioxide, aldehydes and other products

of incomplete combustion.

Products

11. Toxicological Information

Acute Exposure

Respiratory Irritation Aspiration hazard. If material is misted or if vapors are generated from heating,

exposure may cause irritation of mucous membranes and the upper respiratory

tract.

Eve Irritation May cause eye irritation. Vapors formed from heating may cause eye irritation. **Skin Irritation**

May cause skin irritation. Prolonged or repeated direct exposure to the skin

may result in symptoms of irritation and redness, dermatitis or oil acne.

Not expected to cause skin or respiratory sensitization. Sensitization

Component Analysis – LD50 / LC50

Acute Toxicity Estimate (ATE) Values for Product:

Inhalation LC50 Rat mg/L 1 HR **Oral LD50 Rat** >4500 mg/kg **Dermal LD50 Rabbit** >2000 mg/kg

Brad Penn ® Penn-Grade™ High VI R&O AW ISO VG 15 Hydraulic Oil-Blue BP7357

American Refining Group, Inc.

Revision #:4 Page **5** of **7**

*4.7% of the mixture's LC50 is unknown

Chronic Exposure

Target Organ Effects No data available to indicate product or components present at greater than 1%

are chronic health hazards.

Carcinogenicity This product contains mineral oils which are considered to be severely refined

and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP

346 or Modified Ames test.

Mutagenicity No data available to indicate product or any components present at greater than

.1% are mutagenic or genotoxic.

Reproductive ToxicityNo data available to indicate product or any components present at greater than

.1% are a reproductive toxin.

Teratogenicity No data available to indicate product or any components contained at greater

than .1% may cause birth defects.

12. Ecological Information

Component Analysis- Ecotoxicity - Aquatic Life

Duration/Test/Species Concentration/Conditions

96 Hr LC50 N/A mg/L

Pimephales promelas

DegradabilityNot determinedBioaccumulationNot determinedSoil MobilityNot determined

13. Disposal Considerations

Disposal Instructions

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

14. Transportation Information

Emergency Response Guide No. 128 North American Emergency Response

Guide Book

UN Number Shipping Name (technical name) Hazard Class Packing Group

U.S. DOT Not Regulated

Bulk

U.S. DOT Not Regulated

Non-Bulk

15. Regulatory Information

Revision #:4

Page **6** of **7**

15. Regulatory Information

SARA Extremely Hazardous Substances (Sections 302 & 304) This product does not contain greater than 1% of any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B. This product does not contain greater than 1.0% of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SARA Section 313

rai

SARA Section 311 & 312 Classifications

Acute Hazard No
Chronic Hazard No
Fire Hazard No
Reactivity Hazard No

CERCLA

This product does not contain any "hazardous substances" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

California Prop 65

This product does not intentionally contain any chemicals known to the state of

CA to cause cancer and/or birth defects

Clean Water Act / Oil

Pollution Act

This product contains petroleum distillates and may be subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National

Response Center at 1-800-424-8802.

Global Chemical Inventories

Inventory	Component
	All components
US TSCA	Present
EU	Present
Japan	Not available
Australia	Present
New Zealand	Present
Canada	Present
Switzerland	Not available
Korea	Present
Philippines	Present
China	Present
Taiwan	Not available

16. Other Information

US NFPA Ratings

Health	Fire	Instability
1	1	0

Revision #:4 Page **7** of **7**

16. Other Information		
HMIS Ratings		
II a a l 4 la	Eine.	Dl

Health	Fire	Physical Hazards
1	1	0

Precautionary Labels

Signal Word WARNING!

Harmful if swallowed. Can enter lungs and cause damage.

May cause skin irritation May cause eye irritation

May cause respiratory tract irritation

Preparation/Revision Date 6/15/2012

Revision Reason Outdated MSDS

Prepared By: Katie Vecellio, EHS Intern

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS