

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CAM2 Dexron[®] VI Multi-Vehicle Full Synthetic ATF SYNONYMS: Full synthetic lubricating oil PRODUCT CODE: 80565-298 Automatic Transmission Fluid PRODUCT USE: MANUFACTURER'S NAME: CAM2 International, LLC ADDRESS: 685 Haining Road Vicksburg, MS 39183 USA UNITED STATES: EMERGENCY TELEPHONE NUMBER: 1 800 633 8253 INTERNATIONAL: 1 801 629 0667 These numbers are for emergency use only. If you desire non-emergency product information, please call phone number listed below. **CUSTOMER SERVICE:** 800-338-2262 MSDS FORM NUMBER: 80565-298

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE Red fluid, hydrocarbon odor

CAUTION!

HEALTH HAZARDS

May be harmful if swallowed. May irritate eyes and skin.

POTENTIAL HEALTH EFFECTS

INHALATION This product is not likely to present an inhalation hazard at normal temperatures (BREATHING): and pressures. However, when aerosolizing, misting, or heating of this product, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

EYES: May cause irritation.



SKIN: May cause irritation. Not likely to be absorbed through the skin in harmful amounts.

INGESTION May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and diarrhea. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONSIndividuals with pre-existing respiratory tract (nose, throat, and
lungs) eye and/or skin disorders may have increased susceptibility
to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

POTENTIAL Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment. **EFFECTS:**

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Wt. Percent	Component	Synonym	CAS #
0 - 90	Hydrotreated Distillate, Heavy Paraffin	Highly Refined Synthetic Base Oil	64742-54-7
0 - 90	Hydrotreated Distillate, Light Paraffin	Highly Refined Synthetic Base Oil	64742-55-8
3 - 7	Mineral Oil	Not Available	Mixture
1 - 3	Methacrylate copolymer	Not Available	Proprietary
0.5 - 1.20	Alkoxy Sulfolane	Not Available	Proprietary
0.5 - 1.20	Long-chain alkenyl succinimide	Not Available	Proprietary

SECTION 4: FIRST AID MEASURES

INHALATION
 (BREATHING): Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

- **EYE:** If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.
- **SKIN:** Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists. If product is injected under pressure into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, a physician should immediately evaluate the individual as a medical emergency.

©2009 CAM2 International, LLC



CAM2 DEXRON[®] VI MULTI-VEHICLE FULL SYNTHETIC ATF

INGESTION:
(SWALLOWING)Do NOT induce vomiting. Immediately get medical attention. If spontaneous
vomiting occurs, keep head below hips to avoid breathing the product into the
lungs. Never give anything to an unconscious person by the mouth.

NOTE TO Treat symptomatically and supportively. Treatment may vary with condition **PHYSICAINS:** of victim and specifics of incident.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED):	248°F (120°C) (minimum) (Closed cup Pensky-Martens)
FLAMMABLE LIMITS IN AIR:	Lower: Not Available Upper: Not Available
AUTOIGNITION TEMPERATURE:	Not available
HAZARDOUS COMBUSTION PRODUCTS:	Decomposition and combustion materials may be toxic. Burning may produce smoke, nitorgen oxides, sulfur oxides, carbon dioxide, carbon monoxide and unidentified compounds.
CONDITIONS OF FLAMMABILITY:	Sparks or flame. Products may burn, but does not ignite readily.
EXTINGUISHING MEDIA:	Carbon dioxide, regular foam, dry chemical, water spray, o water fog. Water or foam may cause frothing.
HAZARD RATING 0= LEAST 1= SLIGHT 2= MODERATE 3= HIGH 4= EXTREME	NFPA 704 HAZARD IDENTIFICATIONHEALTH HAZARD (BLUE)1FIRE HAZARD (RED)1REACTIVITY (YELLOW)0SPECIFIC HAZARD (WHITE)
FIRE FIGHTING INSTRUCTIONS:	Keep storage containers cool with water spray. A positive- pressure, self-contained breathing apparatus (SCBA) and full- body protective equipment are required for fire emergencies.
FIRE AND EXPLOSION HAZARDS:	Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Products are not sensitive to mechanical impact or static discharge.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **Section 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain

©2009 CAM2 International, LLC



spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean spark-proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

SECTION 7: HANDLING AND STORAGE

- **HANDLING:** Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing and shoes.
- SHIPPING AND
 STORING:
 Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain residue and can be dangerous.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES Component Exposure Limits

Hydrotreated Distillate, Heavy Paraffin

ACGIĤ:	5mg/m ³ TWA (as Oil Mist, if generated)
	10 mg/m ³ STEL (as Oil Mist, if generated)
OSHA:	5 mg/m ³ TWA (as Oil Mist, if generated)

Hydrotreated Distillate, Light Paraffin

ACGIH: 5mg/m³ TWA (as Oil Mist, if generated) 10 mg/m³ STEL (as Oil Mist, if generated) OSHA: 5 mg/m³ TWA (as Oil Mist, if generated)

Mineral Oil

- ACGIH: 5mg/m³ TWA (related to Oil mist, mineral) 10 mg/m³ STEL (related to Oil mist, mineral) OSHA Final: 5 mg/m³ TWA (related to Oil mist, mineral)
- **ENGINEERING** CONTROLS: Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.



PERSONAL PROTECTIVE EQUIPMENT

- **RESPIRATORY PROTECTION:** No respiratory protection is normally required. Use NIOSH-certified P- or Rseries particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.
- **EYE PROTECTION:** Where eye contact is likely, wear safety glasses; contact lens use is not recommended.
- **SKIN** Where skin contact is likely, wear neoprene, nitrile or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended. When product is heated and skin contact is likely, wear heat-insulating gloves, boots, and other protective clothing.

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

PERSONALUse good personal hygiene. Wash thoroughly with soap and water afterHYGIENE:handling product and before eating, drinking, or using tobacco products. Clean
affected clothing, shoes, and protective equipment before reuse. Discard
leather articles, such as shoes, saturated with these products.

OTHERWhere spills and splashes are likely, facilities storing or using thesePROTECTIVEproducts should be equipped with emergency eyewash and shower,EQUIPMENT:both equipped with clean water, in the immediate work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE, APPEARANCE	Red liquid
ODOR:	Hydrocarbon odor
ODOR THRESHOLD:	Not available
MOLECULAR WEIGHT:	Not applicable
SPECIFIC GRAVITY:	0.847 (Estimated) (water=1) (approximately)
VAPOR DENSITY:	>1 (Air = 1)
VAPOR PRESSURE:	less than 0.1 kPa @ 104°F (40°C)
RELATIVE DENSITY:	0.847 g/cm ³ at 60°F (15.5°C)

©2009 CAM2 International, LLC



MATERIAL SAFETY DATA SHEET

CAM2 DEXRON® VI MULTI-VEHICLE FULL SYNTHETIC ATF

INITIAL BOILING POINT:	Not available
BOILING RANGE	Not available
FREEZING/MELTING POINT:	Not available
pH:	Not applicable
EVAPORATION RATE:	Not available
SOLUBILTY IN WATER:	Insoluble
FLASH POINT:	248°F (120°C) (minimum) (Closed cup Pensky-Martens)
FLAMMABILITY:	Not available
FLAMMABLE LIMITS IN AIR:	LOWER: Not available UPPER: Not available
AUTOIGNITION TEMPERATURE:	Not available

SECTION 10: STABILITY AND REACTIVITY

- **INCOMPATIBILITY:** Avoid strong oxidizing agents and strong reducing agents.
- **REACTIVITY:** Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.

HAZARDOUSNone under normal temperatures and pressures. Also see Section 5:DECOMPOSITIONHAZARDOUS COMBUSTION PRODUCTS.PRODUCTS:

SECTION 11: TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE: Skin, Eyes, Ingestion, and Inhalation.

- ACUTE EFFECTS: May be harmful if swallowed. May cause throat irritation, nausea, vomiting and diarrhea. Aspiration hazard: breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death. May irritate eyes and skin.
- **REPEATED DOSE EFFECTS:** Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

©2009 CAM2 International, LLC



MATERIAL SAFETY DATA SHEET

CAM2 DEXRON® VI MULTI-VEHICLE FULL SYNTHETIC ATF

SENSITIZATION: No information available for this product.

MUTAGENICITY: No information available for this product.

CARCINOGENICITY Based on best current information, there is no known carcinogenicity as regulated by OSHA; as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1 Group 2A, or Group 2B agents as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

REPRODUCTIVE TOXICITY:	No information available for this product.
TERATOGENICITY:	No information available for this product.
NEUROTOXICITY:	No information available for this product.

TOXICITY DATA: Component Analysis – LD50/LC50

Hydrotreated Distillate, Heavy Paraffin

Oral LD50 >5 g/kg Dermal LD50 >2 g/kg Inhalation LC50 >5 mg/L (mist)

Hydrotreated Distillate, Light Paraffin

Oral LD50 >5 g/kg Dermal LD50 >2 g/kg Inhalation LC50 >5 mg/L (mist)

Mineral Oil

Dermal LD50 Rabbit >5000 mg/kg Oral LD50 Rat >5000 mg/kg Inhalation LC50 Rat .2.18 mg/l (Vapor)

Alkoxy Sulfonlane

Dermal LD50 Rabbit 4000 to 8000 mg/kg Oral LD50 Rat >10000 mg/kg

Long-chain alkenyl succinimide

Dermal LD50 Rabbit 5000 mg/kg Oral LD50 Rat >14430 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: Material expected to be harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.

PERSISTENCE/ Not readily biodegradable. **DEGRADABILITY:**

BIOACCUMULATIVE No information available for the product. **POTENTIAL:**

©2009 CAM2 International, LLC



 MOBILITY IN
 Base oil component(s) – Low solubility and floats; expected to

 ENVIRONMENTAL
 migrate from water to the land.

 MEDIA:
 OTHER ADVERSE

 OTHER ADVERSE
 Not available.

OCTANOL/WATER Not available. PARTITION COEFFICIENT:

VOLATILE ORGANIC Negligible COMPOUNDS:

AQUATIC RELEASE: Advise authorities if product has entered or may enter watercourses or sewer drains.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

USEPA WASTE CODES: This product, if discarded, is not expected to be a characteristic or listed hazardous waste. If recycled in the USA, it must be managed in accordance with 40 CFR Part 279. Processing, use, or contamination by user may change the waste code(s) applicable to the disposal of these products.

SECTION 14: TRANSPORT INFORMATION

LAND (DOT): (Shipping Name)	Not regulated as a hazardous material for Land Transport.
LAND (TDG): (Shipping Name)	Not regulated as a dangerous good for Land Transport.
EMERGENCY RESPONSE GUIDE NUMBER:	Not applicable Reference North American Emergency Response Guidebook.

SECTION 15: REGULATORY INFORMATION

USA REGULATIONS

SARA SECTIONSThis product poses the following health hazard(s) as defined in 40 CFR Part311 AND 312370 and is subject to the requirements of sections 311 and 312 of Title III of
Superfund Amendments and Reauthorization Act of 1986 (SARA):

©2009 CAM2 International, LLC



Immediate (Acute) Health Hazard	
Delayed (Chronic) Health Hazard	No
Physical Fire	No
Physical Sudden Release of Pressure	No
Physical Reactive	

SARA SECTION313: This product does not contain chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

CERCLA: This product contains a component that list the following hazardous substances listed pursuant to the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4: RQ (Reportable quantity): Phenol: 1000 lbs. (454 kg); Ethylene glycol 5000 lbs. (2270 kg); Arsenic: 1 lb. (0.454kg); Ethyl acrylate 1000 lbs. (454kg)

- **TSCA:** All components are listed or exempted.
- **CALIFORNIA:** This product contains a component that list the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm: 2-Propenoic Acid, Ethyl Ester, Arsenic, Ethylene oxide.

SECTION 16: OTHER INFORMATION

DATE ISSUED: May 20, 2014

SUPERSEDES: New Issue.

REVISION NO. 0

REVISION INFORMATION: Not applicable.

LABEL/OTHER INFORMATION: Not available.

MSDS FORM NUMBER: 80565-298

-END OF DOCUMENT-

©2009 CAM2 International, LLC

The information in this Safety Sheet was obtained from sources which we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT. This safety sheet was prepared and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.