

## Classic ATF®

Kendall® Classic ATF is a high-quality transmission fluid recommended for use in all domestic and import vehicles no longer under warranty where the OEM previously specified a GM DEXRON® -III H or Ford MERCON® fluid.

Classic ATF is formulated to provide the proper frictional characteristics for smooth, quiet shifting in electronically controlled automatic transmissions. It has excellent oxidation resistance for long fluid life, excellent low-temperature properties for easy shifting in cold weather, protects against wear and helps minimize the formation of sludge and varnish.

### **Applications**

- GM and Ford automatic transmissions in 2005 and earlier model-year vehicles that are no longer under warranty, where the OEM previously specified DEXRON® -III H, DEXRON® -II, DEXRON® or MERCON® ATF
- Import vehicles where DEXRON® -III H (obsolete) or an earlier-generation DEXRON® fluid (obsolete) is specified
- Allison heavy-duty off-highway automatic transmissions that require a C-4 quality fluid
- Hydraulic systems on industrial and mobile equipment operating over a wide temperature range

**Note:** Classic ATF is **not** recommended for use in newer automatic transmissions that require a GM DEXRON® -VI, Ford MERCON® LV, Ford MERCON® SP or Ford MERCON® V fluid for warranty coverage, or in continuously variable transmissions (CVTs).

### **Features/Benefits**

- Proper frictional properties for smooth shifting and excellent anti-shudder performance
- Excellent oxidation resistance and thermal stability for long fluid life
- Excellent low-temperature properties
- Protects against wear
- Minimizes sludge and varnish deposits
- Protects against rust and corrosion
- Good seal compatibility
- Suitable for both automotive and industrial applications

**Transmission  
Fluid For Older  
GM & Ford  
Automatic  
Transmissions**

### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**kendallmotoroil@  
p66.com**

**Classic ATF®****Typical Properties**

Specific Gravity @ 60°F	0.861
Density, lbs/gal @ 60°F	7.17
Color, Visual	Red
Flash Point (COC), °C (°F)	212 (414)
Pour Point, °C (°F)	<-40 (<-40)
Viscosity, Brookfield	
cP @ -40°C	14,000
Viscosity, Kinematic	
cSt @ 40°C	32.1
cSt @ 100°C	7.0
Viscosity Index	188
Zinc, wt %	<0.003

**Health and Safety Information**

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.