

Concrete Form Oils

Low Temp, SUS 65 and SUS 95 (DOT Approved*)

Concrete Form Oils

- Prevents concrete build-up on wood and metal forms.
- Non-residual, non-staining
- Light colored
- Non-drying oily film
- Eliminates 'bug holes'
- Resists water wash-off
- Three viscosity choices for year round application

Application:

Apply to a clean, dry surface with a roller, brush or sprayer.

*Note: Please check federal, state, and local VOC regulations.



	Test Method	65	95	Low Temp
Gravity, API	ASTM D-4052	34.1	32.1	35.8
Density, lbs/gal (g/L)	Calculated	7.13 (851)	7.21 (861)	7.05 (842)
Viscosity, cSt @ 40°C	ASTM D-445	11.40	21.49	8.43
Viscosity, cSt @ 100°C	ASTM D-445	2.88	4.38	2.38
Viscosity, SUS @ 100°F	ASTM D-2161	67.0	112	55
Viscosity, SUS @ 210°F	ASTM D-2161	36.0	41	34
Viscosity Index	ASTM D-2270	99	113	98
Pour Point, °F (°C)	ASTM D-5949	-43 (-42)	-32 (-36)	-43 (-42)
Flash Point, °F (°C)	ASTM D-92	375 (190)	385 (196)	245 (118)
Color	ASTM D-1500	0.5	1.0	1.0
VOC, g/L	EPA Method 24	62	27	133
Product Code		7705	7706	7704

