

AutoTrans Super Plus™



Product Description

AutoTrans Super Plus™ is a fully synthetic high viscosity automatic transmission fluid that supports the performance requirements in a vast majority of today's automatic transmissions, including Allison, BMW, Honda, Ford, Mercedes Benz, Mitsubishi, Nissan, Toyota, Volkswagen, Voith, Volvo, ZF, and many others. **AutoTrans Super Plus™** is suitable for severe service applications (up to 50,000 miles) and for extended drain intervals in normal service applications (up to 100,000 miles). It offers excellent corrosion resistance to all types of metals used in transmissions and hydraulic systems, plus provides superior friction retention and thermal and oxidation stability. **AutoTrans Super Plus™** can be used in a broad variety of multi-vehicle applications found in on- and off- highway service as well as marine and industrial applications.

Product Features and Benefits

Friction modifiers control lock-up rates of clutch packs for proper transmission shifting characteristics and efficient power transfer.

Controls seal deterioration to limit fluid leakage.

Specifically formulated for extra wear control and rust protection for longer equipment life.

Special detergent/dispersant additives limit formation of sludge and varnish deposits which interfere with proper transmission operation.

Multi-grade for optimum performance during cold starts and high temperature operations, including start/stop severe service.

Formulated to be compatible with the metallurgy used in most modern transmissions and high-pressure hydraulic systems.

Provides efficient heat removal from clutch surfaces to extend clutch life and reduce clutch shudder in modulated torque converters.

Full synthetic for longer fluid life and faster oil flow in low temperature operation.

Typical Applications

Supports the performance requirements of:

Aisin Warner AW-1	Ford FNR5	Jaguar WSS-M2C922-A1	Mitsubishi SP-III	Toyota T-IV
Aisin Warner JWS3309	Ford WSS-M2C138	JASO 1-A	Mitsubishi Dia Queen ATF J2	Toyota PSF Type EH
Allison C-4	Ford WSS-M2C922	Jatco Texaco 402	Mitsubishi PS Fluid	Voith H55.6335
Allison TES-295	Ford XL-12	Jatco 3100 PL085	Mitsubishi Diamond SP-III	Volvo 1161621 & 1161521
Allison TES-389B	Ford WSS-M2C195-A	MAN 339-V-1	Nissan Matic C	Volvo 1161640 & 1161540
Audi/VW TL 052 162	GM Auto Trak II	MAN 339-Z-1	Nissan Matic D	Volvo 31256774
Audi/VW TL 052 990	GM IID, GM IIIF, GM IIIG	MAN 339F	Nissan Matic J	Volvo P/N 97340
Audi/VW TL 055 025-A	GM IIHH, GM III	Mazda M-III	Nissan Matic K	Volvo AT 101 (P/N 97341)
Audi/VW Porsche	GM T-IV Transmission Fluid	Mazda M-V	Nissan PSF-II	ZF LifeGuard Fluid 5
000.043.204.63	GM ATF Saturn T-IV	Mercedes Benz 236.1	North American OEM	ZF TE-ML 03D
000.043.205.28	GM AW-1 Transmission Fluid	Mercedes Benz 236.10	High Viscosity ATF	ZF TE-ML 04D
BMW 83 22 0 026 922	GM TASA	Mercedes Benz 236.11	PSA B71 2340	ZF TE-ML 05L
BMW 83 22 9 407 807	GM Power Steering Fluid	Mercedes Benz 236.2	Renault DP-0	ZF TE-ML 09
BMW MINI 83 22 7 542 290	GM 9985010	Mercedes Benz 236.3	Saab 93165147	ZF TE-ML 11 (3 and 4 speeds)
Daihatsu Ammix D-III ATF	GM 9985835	Mercedes Benz 236.5	Saab Power Steering Fluid 2634	ZF TE-ML 14A
FCA ATF+4	Honda ATF-Z1	Mercedes Benz 236.6	Subaru ATF	ZF TE-ML 16L
FCA MOPAR AS68 / 69RC	Hyundai/KIA Red-1	Mercedes Benz 236.7	Subaru ATF HP	ZF TE-ML 17C
FCA Chrysler MS-1872	Hyundai/KIA JWS 3314	Mercedes Benz 236.81	Subaru Power Steering Fluid	ZF TE-ML 21L
FCA Chrysler MS-5931	Hyundai/KIA JWS 3317	Mercedes Benz 236.9	Suzuki 3314	
FCA Chrysler MS-108388	Hyundai/KIA SP-II	Mercedes Benz 236.91	Suzuki 3317	
Ford WSS-M2C924-A	Hyundai/KIA SP-III	Mercedes Benz GL-450	Toyota T	
Ford Merc V	Hyundai/KIA PSF-3	Mitsubishi SP-II	Toyota T-1, T-II & T-III	

Dexron® is a trademark of General Motors Inc.
Mercon® is a trademark of the Ford Motor Company.

NOTE: ATF recommendations may vary between models from manufacturer. Please consult the owner's manual for the correct fluid recommendations.

Typical Properties

SAE Viscosity Grade	J300	
Viscosity		
@ 100°C, cSt	ASTM D445	7.2
@ 40°C, cSt	ASTM D445	34.0
Viscosity Index	ASTM D2270	180
Pour Point, °F (°C)	ASTM D97	-47 (-44)
Flash Point, °F (°C)	ASTM D92	400 (204)
API Gravity, 60°F	ASTM D287	34.6

D-A Part Number:

Bulk	54561
Tote – 330 Gal	54563
Drum – 55 Gal	54562
Pail (Metal) – 5 Gal	54569
Pail (Plastic) – 5 Gal	54568
Case – 12/1 Qt	54566