

# CORROSION PREVENTIVES

## **RUSTOP WD-705** **Solvent-Based, Water** **Displacing Corrosion** **Preventive** **Barium Free**



605 Colby Drive  
Waterloo, Ont. N2V 1A1  
Tel: (519) 884-8455  
Fax: (519) 884-4477  
e-mail: info@lubricorinc.com

### DESCRIPTION:

**RUSTOP WD-705** is a solvent based, water-displacing corrosion preventive formulated to give excellent long term indoor protection. This product dries to a thin, firm amber film. The film is easily cleaned using an alkaline cleaner.

### APPLICATIONS:

For best results **RUSTOP WD-705** should be applied by dipping, especially if water displacement is needed. Spraying or flowcoating is also acceptable if properly functioning. No heating required, APPLY COLD.

### TYPICAL PROPERTIES:

Appearance of.....	Clear, light amber liquid
Specific Gravity @ 68°F.....	0.81
Viscosity @ 100°F, SUS.....	33
Flash point, TCC.....	49°C or 120°F
Film Type.....	Slightly oily to Dry
Suppressor.....	Yes
Water Displacement.....	Yes
Humidity Cabinet .....	15+ days
In-door protection .....	1 to 4 months

### CUSTOMER BENEFITS:

**Excellent Humidity Protection** - when used straight, this product will protect ferrous and nonferrous parts up to 3 months indoor storage.

**Superior Water Displacing Properties** - Displaces free standing water and cleaner solutions, and replaces the water with protective slightly oily film.

**Fingerprint Suppression Properties** - Handled parts are fully protected from fingerprint corrosion.

### HANDLING and STORAGE:

No health or safety hazards exist when **RUSTOP WD-705** is stored, used and disposed of in accordance with instructions given on the Material Safety Data Sheet for this product. Keep container closed after use.

### IMPORTANT:

All variables effecting rust protection cannot be indicated. Abnormal humidity, temperature, sunlight, special handling, special packaging will all effect length of protection and type of protection.

**DESIGNED .... WITH PURPOSE**

The information contained in this bulletin is to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. Lubricor Inc. disclaims any liability incurred in connection with the use of these data and suggestions.