



Mobil 1™ Supercar Series

Mobil Passenger-Vehicle-Lube , United States

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ Supercar Motor Oils are a family of advanced full synthetic motor oil specifically designed for high performance cars to provide exceptional cleaning power and wear protection, and deliver outstanding overall performance. Mobil 1™ Supercar Motor Oils are proven in high performance North American sports cars and suitable for use in everyday driving and high performance track events.

From street to track, Mobil 1™ Supercar Motor Oils have been expertly engineered to prolong engine life in gasoline powered automobiles. We're as passionate about your engine as you are about your car.

Features and Benefits

- Made with a proprietary blend of leading edge components formulated to provide outstanding performance in many driving situations.
- Single oil for street and track use
- Enhanced frictional properties help enable improved fuel economy, higher horsepower and reduced engine wear
- Active cleaning agents help enable lower operating temperatures and longer engine life
- Outstanding thermal and oxidation stability help to reduce oil aging
- Excellent aeration control
- Catalytic converter compatibility (only applicable for Mobil 1™ Supercar 0W-40)

Applications

Mobil 1™ Supercar Motor Oils are recommended by ExxonMobil for General Motors dexosR applications, including high-performance naturally aspirated, turbo-charged, and super-charged gasoline engines.

Specifications and Approvals

This product has the following approvals:	0W-40	5W-50
GM dexosR	X	X

This product meets or exceeds the requirements of:	0W-40	5W-50
API SP		X

Properties and Specifications

Property	0W-40	5W-50
Grade	SAE 0W-40	SAE 5W-50
Calcium, mass%, ASTM D4951	0.17	0.073
Density @ 15.6 C, g/ml, ASTM D4052	0.8408	0.8495
Flash Point, Cleveland Open Cup, °C, ASTM D92	232	230
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.9	18.1
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	69.0	111.8

Property	0W-40	5W-50
Magnesium, mass%, ASTM D4951	0	0.074
Molybdenum, mass%, ASTM D4951	0.008	0.0165
Phosphorus, mass%, ASTM D4951	0.09	0.11
Pour Point, °C, ASTM D97	-51	-48
Total Base Number, mgKOH/g, ASTM D2896	8.5	9.6
Zinc, mass%, ASTM D4951	0.1	0.12

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Exxon Mobil Corporation

22777 Springwoods Village Parkway


Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved