



## **Super-D XA® Diesel Engine Oil with Liquid Titanium®**

Kendall® Super-D XA (eXhaust Advantage) Diesel Engine Oil with Liquid Titanium protection additive is a premium quality, part-synthetic API CJ-4 engine oil developed for use in four-stroke cycle diesel engines designed to meet 2007 and later EPA on-highway exhaust emissions standards. It is specially formulated for compatibility with exhaust aftertreatment devices using diesel particulate filters (DPF), diesel oxidation catalysts (DOC) and/or selective catalytic reduction (SCR). It is backward serviceable for use in pre-2007 diesel engines, and may be used in mixed fleets with both diesel and gasoline-fueled vehicles.

Super-D XA with Liquid Titanium is formulated with a blend of synthetic and high-quality Group II base stocks and a proprietary low-SAPS additive package to provide outstanding engine protection in new and older diesel engines. It is fortified with our exclusive Liquid Titanium® protection additive for enhanced oxidation resistance and protection against wear. This additive enhancement provides increased engine protection from a strongly bonded titanium shield formed on the surface of critical engine parts, which reduces wear and helps extend component life.

Super-D XA with Liquid Titanium has excellent soot dispersancy to protect against abrasive wear and soot-induced oil thickening, and to ensure good low-temperature pumpability even with highly soot-laden oil. It provides excellent bearing corrosion protection and protects against sludge and varnish formation. The synthetic blend formulation provides enhanced thermal stability at high temperatures and improved low-temperature properties compared with conventional diesel engine oils.

Super-D XA with Liquid Titanium meets or exceeds the performance requirements of API Service Categories CJ-4 and SN, and is approved under the latest OEM specifications for use in low-emission diesel engines. It is backward serviceable for use where earlier API "C" category engine oils, or the concurrent earlier OEM specifications, are specified. It is formulated for use in diesel engines operating on diesel fuels with sulfur content up to 500 ppm. However, for applications not using Ultra-Low Sulfur Diesel (ULSD), consult the engine manufacturer for recommended service interval.

**Premium  
Synthetic Blend  
API CJ-4  
Diesel Engine  
Oil; Fortified  
With  
Liquid Titanium®  
Protection  
Additive**



### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**kendallmotoroil@  
p66.com**



## **Applications**

- On-highway diesel trucks equipped with EGR and exhaust aftertreatment systems to meet 2007/2010 emissions standards
- Older diesel equipment with conventional, non-EGR engines or ACERT engines
- Off-highway construction, earth moving and mining equipment
- Mixed fleets with diesel and gasoline-fueled vehicles

Super-D XA with Liquid Titanium is licensed or OEM-certified for:

- API Service CJ-4, CI-4 with CI-4 PLUS, CI-4, CH-4, SN
- Cummins CES 20081
- Detroit Diesel DFS 93K218
- Mack EO-O Premium Plus
- Mercedes-Benz Sheet 228.31 (SAE 15W-40)
- MTU MTL 5044 Type 2.1 (SAE 15W-40)
- Renault VI RLD-3
- Volvo VDS-4

Super-D XA with Liquid Titanium meets or exceeds the requirements of:

- ACEA E9-08, E7-08 (SAE 15W-40)
- Caterpillar ECF-3, ECF-2, ECF-1-a
- Chrysler MS-10902 (SAE 15W-40)
- Ford WSS-M2C171-E
- JASO DH-2 (SAE 15W-40)
- Mercedes-Benz Sheet 228.3 (SAE 15W-40)
- Diesel engines manufactured by OEMs not listed above, where the OEM specifies API CJ-4 engine oil

## **Features/Benefits**

- Excellent protection for newer low-emission diesel engines and older diesel engines
- Specially formulated to protect exhaust aftertreatment systems
- Exclusive Liquid Titanium® protection additive provides enhanced oxidation resistance and protection against engine wear
- Outstanding soot control for protection against abrasive wear and soot-induced oil thickening
- Outstanding resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust and bearing corrosion
- Excellent low-temperature pumpability with soot-laden oil
- High shear stability
- Good resistance to foaming and aeration

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2013 Phillips 66 Company. Kendall, the Two Finger logo, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.

## Super-D XA® Diesel Engine Oil with Liquid Titanium®

### Typical Properties

SAE Grade	10W-30	15W-40
Specific Gravity @ 60°F	0.872	0.877
Density, lbs/gal @ 60°F	7.26	7.30
Color, ASTM D1500	L 4.0	4.0
Flash Point (COC), °C (°F)	226 (439)	229 (444)
Pour Point, °C (°F)	-40 (-40)	-40 (-40)
Viscosity, Kinematic		
cSt @ 40°C	79.0	117
cSt @ 100°C	12.2	15.3
Viscosity Index	151	137
Cold Cranking Viscosity, cP	6,300	6,000
@ (°C)	(-25)	(-20)
High-Temp/High-Shear Viscosity, cP @ 150°C	3.6	4.4
Sulfated Ash, ASTM D874, wt %	0.95	0.95
Total Base Number (TBN), ASTM D2896	9.5	9.5
Titanium, wt %	0.010	0.010
Zinc, wt %	0.126	0.126

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.