



SUPER SYNTHETIC XL MOTOR OIL

Super Synthetic XL Motor Oils are specially formulated using synthetic base oils and high performance additive packages to provide superior performance benefits over conventional engine oils. These oils are formulated for excellent oxidation stability for long product life, superior low-temperature properties to insure protection during cold starts, lower volatility for reduced oil consumption, and excellent resistance to viscosity breakdown.

Super Synthetic XL Motor Oils meet the most demanding lubrication requirements of today's naturally aspirated, turbocharged and supercharged gasoline fueled and flex-fueled engines. These oils exceed the requirements of API SN, ILSAC GF-5 and are "Resource Conserving" for improved fuel economy.

TYPICAL CHARACTERISTICS

SAE GRADE	0W-20	5W-20	5W-30
Viscosity @ 40 °C, cSt	43.5	44.0	62.0
Viscosity @ 100 °C, cSt	8.3	8.3	11.0
Viscosity Index (Min.)	170	165	165
Pour Point, °C	-45	-45	-45
CCS, cP @ °C	5250 @-35°C	4100 @-30°C	5000 @-30°C
NOACK, wt%	13	12.5	11
HTHS @ 150 °C Viscosity, cP	2.6	2.6	3.0
Zinc, wt%	0.085	0.085	0.085
Phosphorus, wt%	0.077	0.077	0.077

PROPERTIES AND PERFORMANCE

- API SN
- ILSAC GF-5
- Chrysler MS-6395 (5W-20 and 5W-30)
- Ford WSS-M2C945-A (5W-20)
- Ford WSS-M2C946-A (5W-30)
- Honda (0W-20)

AVAILABLE PACKAGING: Bulk, Totes, Drums, Pails, Cases

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.

Eni USA R&M Co. Inc.

Pennsylvania–Ohio–West Virginia 1-800-922-9243
New Jersey 1-800-543-9556
New York 1-800-632-8777
Canada 1-800-957-2447

Rev. 4/20/11
Supersedes 12/11/09

Page 1 of 1