# **VersaTrans® ATF**

Kendall<sup>®</sup> VersaTrans ATF is a premium quality, synthetic blend transmission fluid specially designed for use in automatic transmissions in most passenger cars and light trucks. It has been extensively field tested for use in most North American vehicles and in a wide variety of European and Japanese vehicles.

VersaTrans ATF has carefully balanced frictional properties for smooth shifting and excellent anti-shudder performance. It has high shear stability and excellent oxidation resistance for long service life. It provides excellent wear protection, helps protect against sludge and varnish formation, and has excellent low-temperature properties for easier shifting in cold weather. The part-synthetic formulation provides enhanced performance benefits at extreme temperatures compared with conventional, all-mineral transmission fluids.

VersaTrans ATF meets the requirements of the JASO M315, Class 1A performance standard developed by Japanese automakers for service fill automatic transmission fluids.

#### **Applications**

- Chrysler automatic transmissions, except continuously variable transmissions (CVTs)
- Ford automatic transmissions where MERCON<sup>®</sup> V or an earlier-generation MERCON<sup>®</sup> fluid (obsolete) is specified
- GM automatic transmissions in 2005 and earlier vehicles, except those that require DEXRON<sup>®</sup> -VI for warranty coverage, or a CVT fluid
- Many import vehicles, including Acura, Audi, BMW, Honda, Hyundai, Infiniti, Kia, Mazda, Mercedes-Benz, Mitsubishi, Nissan, Porsche, Saab, Saturn, Toyota, Volkswagen and Volvo<sup>(1)</sup>
- Heavy-duty automatic and powershift transmissions in trucks and buses
- Hydraulic systems on industrial and mobile equipment operating over a wide temperature range

<sup>(1)</sup>**Note:** VersaTrans ATF is <u>not</u> recommended for use in continuously variable transmissions (CVTs) or in most 6-speed or 7-speed automatic transmissions. For questions about a specific application, please call our Technical Support Hotline.

Synthetic Blend Multi-Vehicle Automatic Transmission Fluid

\delta Kendali.

#### CONTACT INFORMATION

#### Phillips66 Lubricants.com

U.S. Customer Service: **1-800-368-7128** 

Technical Hotline: 1-877-445-9198

International Customer Service: 1-832-765-2500

E-mail address: kendallmotoroil@ p66.com



VersaTrans ATF is OEM-approved for service fill in the following applications:

- Ford MERCON<sup>®</sup> V (License Nos. M5091007, M5091008, M5091009)
- Voith DIWA transmissions

VersaTrans ATF is recommended for service fill in the following applications:

- Allison automatic transmissions in off-highway applications where a C-4 quality fluid is specified
- ZF Ecomat transmissions

## Features/Benefits

- Extensively field-tested in a wide variety of domestic and import vehicle automatic transmissions
- Proper frictional properties for smooth shifting and excellent anti-shudder performance
- · Excellent oxidation resistance and thermal stability for long fluid life
- · Protects against sludge and varnish formation
- · Protects against wear
- Protects against rust and corrosion
- · Excellent low-temperature properties for easier shifting in cold weather
- · Good seal compatibility
- Good foam resistance

### VersaTrans® ATF

Typical Properties	
Specific Gravity @ 60°F	0.857
Density, Ibs/gal @ 60°F	7.14
Color, Visual	Red
Flash Point (COC), °C (°F)	196 (385)
Pour Point, °C (°F)	<-45 (<-49)
Viscosity, Brookfield	
cP @ -40°C	10,200
Viscosity, Kinematic	
cSt @ 40°C	34.0
cSt @ 100°C	7.6
Viscosity Index	202
Zinc, wt %	<0.001

#### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via *http://w3apps.phillips66.com/NetMSDS*.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

<sup>© 2014</sup> Phillips 66 Company. Kendall, the Two Finger logo, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.